

## Salt Spray TEST REPORT

料號 (Part No.)	NAR20- AK6110&NAW1 0-AK5V200	測試日期 (Date)	2014.09.25	測試儀器 (Equipment)	Salt Spray Tester Equipment No. :F-01403	溫度 (Temp.)	20°C
品名 (Part Name)	USB TYPEC	報告號 (Report No.)	SZAMC-Q1409-0108	測試群組 (Group)	<b>K</b>	濕度 (Hum.)	56%
<b>Subject mated connectors at 35°C with 5-salt-solution Concentration.</b>							
項目 Item		試驗條件 Test condition		試驗記錄 Test record			
試驗室溫度 Test chamber temperature		35°C±1°C		35.2°C			
飽和空氣溫度 Saturation air temperature		47°C±1°C		47.1°C			
試驗室相對濕度 Relative humidity of test chamber		≥85%RH		90%			
壓縮空氣壓力 Compressed air pressure		1±0.01Kg/Cm <sup>2</sup>		1.0Kg/Cm <sup>2</sup>			
鹽水溶液PH值 PH of salt solution		6.5 ~ 7.2		6.8			
鹽水溶液比重 Weight of salt solution		1.025 ~ 1.045		1.036			
鹽霧量 Salt spray volume		1 ~ 2ml/80Cm <sup>2</sup> /h		1.6ml/80Cm <sup>2</sup> /h			
鹽水桶容量 Volume of salt solution bareel		25L		實際添加:9.6L			
<b>Requirement: No physical damage after testing</b>							
試驗時間 Test Duration	試驗狀況 Test statement			樣品數量 Sample Size	判定 Check		
48H	樣品48H 鹽霧測試,樣品表面無異常現象.			10PCS	OK		
備注(Remark): Accept							
核准 (Approved By)	張聰雲	審核 (Checked by)	易小亮	檢驗者 (Tested By)	彭彪彪		